



Universal Drill & Cutter Grinder

ORDER NO.VDG-32N CODE NO.8001-010



VERTEX®



Double cams: The cam of grinding drills & The cam of grinding taps.



FEATURES

- Grinding capacity: $\varnothing 1.5\sim\varnothing 32\text{mm}$ (Straight shank & taper shank) double wheels. It only need to rotate the motor when want to grind the tool of different material. It can increase the safety & save the time for changing & repairing the grinding wheel.
- The kinds of grinding tool include: drills, step drills, taps, lips of end mills, round bars, etc.
- Adopts precision 4" 6 pawl self-centering chuck, clipping one time. It can grind the blade of drills and do the paring of drills abdomen. The angle of drills both sides and the length of the blade are the same after grinding. It can keep the accuracy of the center of drills without off center.

Longitudinal travel of table	120mm
Cross travel of saddle	135mm
Rotary angle of wheel head	360°
Point angle	90°-180°
Size of wheel	125x50x31.75mm
Speed of wheel	3600 RPM
Motor	3/4HP, 110V/220V/380V
N.W. / G.W.	90kgs/120kgs
Size of packing (LxWxH)	800x550x670mm



Horizontal Band Saws

ORDER NO.HBS-7 CODE NO.8001-030



Please notify the voltage & phase when you ordering.

SPECIFICATION

Capacity	● 180mm (7") ■ 180x300mm (7"x12")
Blade size	19x0.9x2360mm (3/4"x0.32x7'9")
Motor	1HP 4pole 50HZ/1430rpm; 60HZ/1720rpm
Blade speed	22, 33, 45, 65mpm (86-132-178-260fpm)
Machine dim	L1470xW430mm (L58"xW17") H990mm (39") horizontal position.
N.W.	130kgs (286LBS)
G.W.	150kgs (341LBS)



Horizontal Band Saws

ORDER NO.HBS-7CE CODE NO.8001-030CE



SPECIFICATION

Capacity	90° ● 180mm ■ 180x280mm ■ 65x300mm 45° ● 110mm ■ 180x110mm
Blade size	19x0.9x2360mm
Motor	1HP 4pole 50HZ/1430rpm; 60HZ/1720rpm
Blade speed	Step pulley 22, 33, 45, 65mpm
Packing Measurement	1295x457x1028mm
N.W. / G.W.	130kgs/150kgs
Type	"CE" Standard