

Manual metal-cutting circular saw

MKS 315 N

Two speeds and miter-swiveling saw head and vice

Article number >

3620303

Brand v

Metallkraft

Availability >

In stock

Immediate delivery

Catalog directory >

Metalworking machines » Metal circular saws » Metal circular saws manually » MKS 315 N

Purchase v

Minimum 1 pc(s).

Delivery content >

- Coolant system
- Length stop 500 mm
- · operating tool
- without saw blade
- without substructure

Shipping informations >

Packaging Metrics	S	Weights		Delivery		Other	
Length	770 mm	Gross	165 kg	Delivery	Carrier	DualUse	×
Width	780 mm	Net	165 kg	Content	1 pc(s).	SCIP	434f9190- 5a1d-4d87- 9e24- bd287d9501d4
Height	850 mm					SVHC	Complex article

Root data 🗸

Country of origin	EAN	Custom number	Quantity unit
ltaly	4036351002918	84615011	pc(s).







Description ~

- two cutting speeds
- Rotatable machine head 45 ° to the left and 45 ° to the right
- Reduction gear running in oil bath
- Automatic membrane coolant pump with standard coolant filter
- Quick-action vise with antigraking device, swiveling 45 ° to the left and 45 ° to the right
- Vise longitudinally displaceable and thus suitable for longitudinal cuts and slits
- · Movable guard ensures optimum safety when cutting
- Control handle with safety switch
- Electrical system in low voltage 24 volts, with emergency stop switch, main switch, speed selector switch and overload protection
- Quality Made in Europe

Media informations >



Technical data v

General features			
Saw blade speed(s)	40/80 min ⁻¹	Saw blade diameter	315 mm
Miter angle	-45 – +45 °		
Dimensions and weights			
Length (product) approx.	1000 mm	Width/depth (product) approx.	1150 mm
Height (product) approx.	1475 mm	Net weight approx.	165 kg
Electrical Data			
Drive motor output	1.5 / 2.2 kW	Supply voltage	400 V
Mains frequency	50 Hz		
Cutting capacity			

Cutting capacity 0° (round) solid material	55 mm	Cutting capacity 0° (round) pipe	90 mm
Cutting capacity 0° (square) pipe	80 x 80 mm	Cutting capacity 0° (rectangle) pipe	115 x 70 mm
Cutting capacity -45° (round) solid material	50 mm	Cutting capacity -45° (round) pipe	80 mm
Cutting capacity -45° (square) pipe	70 x 70 mm	Cutting capacity -45° (rectangle) pipe	70 x 70 mm
Cutting capacity +45° (round) solid material	50 mm	Cutting capacity +45° (round) pipe	80 mm
Cutting capacity +45° (square) pipe	70 x 70 mm	Cutting capacity +45° (rectangle) pipe	70 x 70 mm

Accessories v



Drilling and cutting emulsion AQUACUT B, 5 I

Article number Availability Blocked article Purchase > Minimum 1 can **/metallkraft**

Price informations > Revoked article



Cutting oil BIOCUT, 5 I

3601751

Article number > 3608020

Availability > In stock Immediate delivery Purchase > Minimum 1 can Price informations >

/metallkraft



Substructure MUB 2

Article number V Availability V 3643171

In stock Immediate delivery Purchase > Minimum 1 pc(s). **/metallkraft***

Price informations >



Saw blade HSS-DMo5 Ø 315 x 2.5 x 32 mm t4

Article number V Availability V 3653154

In stock Immediate delivery Purchase > Minimum 1 pc(s). Price informations >

/metallkraft



Saw blade

HSS-DMo5 Ø 315 x 2.5 x 32 mm t6

3653156

Article number V Availability V In stock Immediate delivery Purchase > Minimum 1 pc(s). Price informations >

/metallkraft



Saw blade HSS-DMo5 Ø 315 x 2.5 x 32 mm t8



Article number Availability 3653158

In stock Immediate delivery Purchase > Minimum 1 pc(s). Price informations >



Swarf remover CHIPMAG

Article number Availability 3850010

In stock Immediate delivery

Purchase > Minimum 1 pc(s). Price informations >

/metallkraft



Mounting microdosing unit

Article number Availability 9002000

In stock Immediate delivery Purchase > Minimum 1 pc(s). **/metallkraft**

Price informations >



Drilling and cutting emulsion AQUACUT B Pro, 5 I

Article number Availability 3601752

In stock Immediate delivery

Purchase > Minimum 1 can (5 liter(s))

Price informations >

/metallkraft

Prices on this data sheet are recommended retail prices, subject to change, in €, plus VAT at the statutory rate, plus packaging, shipping, transport, unloading, assembly and, if applicable, instruction costs. Sales prices of the dealers can deviate. No liability is accepted for printing errors, mistakes or incorrect presentation. Technical and optical changes are reserved. Illustration partly with optional accessories.