DATASHEET

Metal band saw

OPTIsaw S 275N

Metal band saws with swivel saw bow. S 275NV with continuously adjustable saw blade speed

OPTIMUM® MASCHINEN - GERMANY

Article number >

3300260

Brand >

Optimum

Availability >

In stock Immediate delivery

Catalog directory >

Metalworking machines » Metal band saws » Swing frame metal band saws » OPTlsaw S 275N / OPTlsaw S 275NV

Purchase v

Minimum 1 pc(s).



Delivery content ✓

- material stop
- · Bi-metal saw band
- substructure
- Coolant pump

Shipping informations >

Packaging Metrics		Weights		Delivery		Other	
Length	1,360 mm	Gross	200 kg	Delivery	Carrier	DualUse	×
Width	590 mm	Net	185 kg	Content	1 pc(s).	SCIP	n/a
Height	900 mm					SVHC	No

Root data 🗸

Country of origin	EAN	Custom number	Quantity unit
Taiwan	4030635028588	84615019	pc(s).



Description ~

- Silent run
- Stable cast execution
- High cutting accuracy due to vibration-free running
- Lowering of the saw arm via hydraulic cylinder with throttle valve infinitely adjustable
- · Micro switch for automatic limit switch
- Coolant system
- As standard with high-quality bi-metal saw band
- · Adjustable material stop for serial work
- Robust machine base
- Ball bearing saw band guide
- Quick-action vice adjustable by handwheel. Clamping the workpiece with a handy quick release lever
- Easy to read scale for angle adjustment
- Overload protection

S 275N

- · Motor protection switch
- Two switchable speeds

S 275NV

- Continuously adjustable saw band speed 20 90 m / min.
- Speed change possible during operation

Manometer

• Easy and correct adjustment of saw blade tension

Media informations >



Fig.: S 275N



Saw belt tension

• Easy and correct adjustment of saw blade tension by means of pressure gauges



Quick clamp vice

- Adjustable via hand wheel
- Clamp the workpieece with handy quick clamp lever

Technical data v

Dimensions and weights			
Length (product) approx.	1400 mm	Width/depth (product) approx.	685 mm
Net weight approx.	185 kg	Max. width/depth (product) approx	985 mm
Height max. (product) approx.	1700 mm		
Electrical Data			
Drive motor output	1.1 kW	Supply voltage	400 V

Mains frequency	50 Hz	Engine power coolant pump	90 W
Machine data			
Saw band speed(s)	45 / 90 m/min	Saw band length	2480 mm
Saw band width	27 mm	Saw band thickness	0.9 mm
Cutting angle	0 – 60 °	Feed	infinitely variable
Lifting the saw bow	Manual		
Cutting ranges			
Cutting range 0° round (solid material)	225 mm	Cutting range 0° square (solid material)	190 mm
Cutting range 0° rectangular lying (solid material)	150 x 245 mm	Clamping range +45° round (full material)	145 mm
Cutting range +45° square (solid material)	150 mm	Cutting range +45° rectangular horizontal (solid material)	190 x 150 mm
Cutting range +60° round (solid material)	90 mm	Cutting range +60° square (solid material)	90 mm
Cutting range +60° rectangular horizontal (solid material)	120 x 90 mm		

Accessories v



Cutting and drilling emulsion AQUACUT C1



Article number V Availability V 3530030

Blocked article

Purchase > Minimum 1 pc(s). Price informations > Revoked article



Saw band

HSS Bi-Metal M 42, 2480 x 27 x 0.9 mm, 5 -8 ZpZ, 0°



Article number V Availability V Purchase > 3357511 In stock Minimum 1 pc(s). Immediate delivery

Price informations >



Saw band

HSS Bi-Metal M 42, 2480 x 27 x 0.9 mm, 5 -8 ZpZ, 6°



Article number Availability Purchase > 3357512 In stock Minimum 1 pc(s). Immediate delivery

Price informations >



Saw band

HSS Bi-Metal M 42, 2480 x 27 x 0.9 mm, 6 -10 ZpZ, 0°



Article number > Availability > Purchase > 3357524 In stock Minimum 1 pc(s).

Immediate delivery



Saw band

HSS Bi-Metal M 42, 2480 x 27 x 0.9 mm, 10 -



OPTIMUM°

OPTIMUM[®]

Article number Availability 3357510

Order-related purchase

Purchase > Minimum 1 pc(s). Price informations >



Saw band

HSS Bi-Metal M 42, 2480 x 27 x 0.9 mm, 10 -14 ZpZ, 0°

Article number **∨** Availability **∨** 3357525 In stock Immediate delivery Purchase > Minimum 1 pc(s). Price informations >



Sawband set for metal band saws

HSS 2,480 x 27 x 0.9 mm

Article number V Availability V 3357504 In stock Immediate delivery Purchase > Minimum 1 pc(s). Price informations >



Height-adjustable material stand

Height-adjustable material stands MSR as a manual aid for supporting and moving workpieces on metal saws. H version

variably adjustable up to 1,050 mm Article number > Availability > 3357610

Purchase > In stock Minimum 1 pc(s). Immediate delivery

OPTIMUM°

Price informations >



Carrying rollers for material stands

PVC rollers

Article number V Availability V Purchase > 3357609 In stock Minimum 1 pc(s).

Immediate delivery

OPTIMUM°

Price informations >



Connection plate

For attachment to height-adjustable material stands

Article number Availability Purchase > 3357005 In stock Minimum 1 pc(s). Immediate delivery

Price informations >

OPTIMUM[®]



Table extension with alternating role MSR 1

OPTIMUM

OPTIMUM®

OPTIMUM[®]

OPTIMUM[®]

MASCHINEN - GERMANY

OPTIMUM[®]

Article number ➤ 3357006

Availability Pu In stock Mi Immediate delivery

Purchase ✓ Minimum 1 pc(s).

Price informations >



Length measuring system

LMS 10

Digital cutting and length measuring systems for attachment to material stand MSR. For the perfect length measurement and exact positioning

Article number V A
3383851 In

Availability ✓ Purchase ✓
In stock Minimum 1 pc(s).
Immediate delivery

Price informations >



Length measuring system

LMS 20

Digital cutting and length measuring systems for attachment to material stand MSR. For the perfect length measurement and exact positioning

Availability
In stock
Immediate delivery

Purchase ✓ Minimum 1 pc(s).

Price informations >



Height-adjustable material stand

MSR 7

Height-adjustable material stands MSR as a manual aid for supporting and moving workpieces on metal saws. H version variably adjustable up to 1,050 mm

Article number ✓ Availability ✓ 3357611 In stock

In stock
Immediate delivery

Purchase ✓ Minimum 1 pc(s). Price informations >



Height-adjustable material stand

MSR 10

Height-adjustable material stands MSR as a manual aid for supporting and moving workpieces on metal saws. H version variably adjustable up to 1,050 mm

Immediate delivery

Availability
In stock

Purchase ✓ Minimum 1 pc(s). Price informations >


© 2023 Stürmer Maschinen GmbH


Page 6 of 7



Length measuring system

LMS 30





Availability
Delivery time on request

Purchase ✓ Minimum 1 pc(s). Price informations >

OPTIMUM[®]



Length measuring system

1 MS 40

Digital cutting and length measuring systems for attachment to material stand MSR. For the perfect length measurement and exact positioning

Article number ✓ Av 3383854 De

Availability V
Delivery time on request

Purchase ✓ Minimum 1 pc(s). Price informations >



Cutting and length measuring system

LMS 1M (1,300 mm)

For mounting on MSR material stands. For perfect length measurement and exact positioning.

Article number ✓ Availability ✓ Purchase ✓
3383841 In stock Minimum 1 pc(s).
Immediate delivery

OPTIMUM[®]
MASCHINEN - GERMANY

Price informations >



Cutting and length measuring system

LMS 2M (2,300 mm)

For mounting on MSR material stands. For perfect length measurement and exact positioning.

Article number ✓ Availability ✓ Purchase ✓
3383842 In stock Minimum 1 pc(s).
Immediate delivery

OPTIMUM®

MASCHINEN - GERMANY

Price informations >



Leveling plate

SE₂

Article number **→** 3381016

Availability
In stock
Immediate delivery

Purchase ✓
Minimum 10 pc(s).

Price informations >

OPTIMUM[®]

Prices on this data sheet are recommended retail prices, subject to change, in €, plus VAT at the statutory rate, plus packaging, shipping, transport, unloading, assembly and, if applicable, instruction costs. Sales prices of the dealers can deviate. No liability is accepted for printing errors, mistakes or incorrect presentation. Technical and optical changes are reserved. Illustration partly with optional accessories.