

DATASHEET

Disc sander

OPTIgrind TS 305

For surface treatment of metals

Article number v 3310305

Brand ✓ Optimum

Availability v In stock Immediate delivery

Catalog directory v

Metalworking machines » Grinding and polishing machines for metal » Belt and disc sanders » Disc sanders

Purchase 🗸

Minimum 1 pc(s).

Delivery content v

- Adjustable angle stop
- sanding sheet

Shipping informations ~

Packaging Met	rics	Weights		Delivery		Other	
Length	455 mm	Gross	26 kg	Delivery	Carrier	DualUse	×
Width	400 mm	Net	25 kg	Content	1 pc(s).	SCIP	n/a
Height	385 mm					SVHC	No

Root data 🗸

Country of origin	EAN	Custom number	Quantity unit
* China	4030635000577	84601900	pc(s).







Description 🗸

- Versatile application areas
- For roughing, fine and form grinding
- Machine body stable and stable
- Balanced aluminum grinding plate for smooth running
- Powerful engine
- Delivery with glued on sanding disc sanding sheet
- Standard extraction nozzle with two diameters for connecting a suction device, outside diameter $\pm Ø 30 / Ø 38$ mm
- Standard miter fence can be swiveled up to ± 60 $^\circ$
- Sanding table inclinable up to ± 45 °
- Velcro pad for grinding wheel available in optional accessories. Grinding wheel adheres very well and can be easily replaced

Media informations v



• Optional accessory (article no.: 3357801). Grinding wheel adheres very well and can be easily replaced





Mitre stop

- Standard miter fence can be tilted up to ± 60
- Grinding table inclinable up to ± 45

- Standard suction nozzle with two diameters for connection of a suction device
- Nominal width outside ± Ø 30/ Ø 38 mm

Technical data 🗸

Dimensions and weights			
Length (product) approx.	440 mm	Width/depth (product) approx.	445 mm
Height (product) approx.	365 mm	Net weight approx.	30 kg
Work table			
Workpiece support width	155 mm	Workpiece support length	440 mm
Workpiece support swivel range	± 45 °	Angle stop adjustment range	± 60 °
Electrical Data			
Drive motor output	0.9 kW	Supply voltage	230 V
Mains frequency	50 Hz	Motor speed(s)	1420 min 1
Sanding machine			
Grinding disc diameter	305 mm		
Grinding wheel(s)			
Speed	1420 min 1		
Sanding attachment			
Extraction duct nominal width	30/38 mm		
Extraction			
Extraction duct nominal width outside	38 mm	Extraction duct nominal width inside	30 mm

Accessories 🗸

	-	Purchase ∨ Minimum 1 pc(s).	Price informations V
	ailability ∨ stock		Price informations V
	ailability ∨ stock		Price informations V
	ailability ∨ stock	Purchase ↓ Minimum 1 PU (5 pc(s).)	Price informations V
	ailability ❤ stock		Price informations V
	ailability ❤ stock		Price informations V
	ailability ∨ stock		Price informations

	Sanding sheet Ø 300 mm, K 1	80, Velcro faste	ener	MASCHINEN - GERMANY
O	Article number ✓ 3357866	Availability V In stock Immediate delivery	Purchase ✓ Minimum 1 PU (5 pc(s).)	Price informations V
I OI	Sanding sheet Ø 300 mm, K 2	240, Velcro faste	ener	MASCHINEN - GERMANY

Prices on this data sheet are recommended retail prices, subject to change, in €, plus VAT at the statutory rate, plus packaging, shipping, transport, unloading, assembly and, if applicable, instruction costs. Sales prices of the dealers can deviate. No liability is accepted for printing errors, mistakes or incorrect presentation. Technical and optical changes are reserved. Illustration partly with optional accessories.