DATASHEET

Double grinding machine

OPTIgrind GU 25

A quality product for trade and industry

Article number >

3101525

Brand >

Optimum

Availability >

In stock

Immediate delivery

Catalog directory >

Metalworking machines » Grinding and polishing machines for metal » Bench grinders

Purchase v

Minimum 1 pc(s).

Delivery content ✓

- Grinding wheel normal corundum coarse K36
- Grinding wheel normal corundum fine K80

Shipping informations >

| Packaging Metrics | | Weights | | Delivery | | Other | |
|-------------------|--------|---------|---------|----------|----------|---------|-----|
| Length | 650 mm | Gross | 34.5 kg | Delivery | Carrier | DualUse | × |
| Width | 390 mm | Net | 32.5 kg | Content | 1 pc(s). | SCIP | n/a |
| Height | 390 mm | | | | | SVHC | No |

Root data 🗸

| Country of origin | | EAN | Custom number | Quantity unit | |
|-------------------|---------|---------------|---------------|---------------|--|
| | * China | 4030635028830 | 84602990 | pc(s). | |







Description >

- Heavy, durable industrial design with maintenance-free motor
- Housing made of extruded aluminum
- Long service life and smooth running due to balanced rotor with quality ball bearings
- Spark protection on each grinding wheel reduces flying sparks
- Sight glasses made of shatterproof material
- Vibration damping rubber feet
- Coarse and fine grinding wheel (K36/K80) as standard

Media informations **∨**





Spark protection

- on each grinding wheel reduces flying sparks and is made of shatterproof material
- tight fitting and easily adjustable

Technical data >

| Dimensions and weights | | | |
|---------------------------------|--------|-------------------------------|------------------------|
| Length (product) approx. | 471 mm | Width/depth (product) approx. | 320 mm |
| Height (product) approx. | 365 mm | Net weight approx. | 33 kg |
| Electrical Data | | | |
| Drive motor output | 1,5 kW | Supply voltage | 400 V |
| Mains frequency | 50 Hz | | |
| Grinding wheel(s) | | | |
| Grinding disc external diameter | 250 mm | Grinding disc width | 40 mm |
| Grinding disc drill hole | 32 mm | Speed | 2850 min 1 |
| Sanding attachment | | | |
| Extraction duct nominal width | 34 mm | | |

Accessories v



Machine substructure with extraction

GU 1 (400 V)

Integrated cyclone extraction with automatic switch



In stock Immediate delivery Purchase > Minimum 1 pc(s). Price informations >



Suction tube

flexible, 2-part

Article number > 3107111

Availability > Purchase > In stock Minimum 1 PU Immediate delivery

Price informations >

OPTIMUM°

OPTIMUM[®]

OPTIMUM[®]

OPTIMUM°

OPTIMUM°



Substructure

GU₃

Article number > Availability > 3107118

In stock Immediate delivery Purchase > Minimum 1 pc(s). Price informations >



Wall bracket

for OPTIgrind QSM 150 to SM 250

Article number > Availability > 3107050

In stock Immediate delivery Purchase > Minimum 1 pc(s). Price informations >



Normal corundum grinding wheel

Ø 250 x 40 Ø 32 mm, K36

Article number > Availability > 3107250

In stock Immediate delivery Purchase > Minimum 1 pc(s).

Price informations >



Normal corundum grinding wheel

Ø 250 x 40 Ø 32 mm. K80

Article number > Availability > 3107255

In stock Immediate delivery Purchase > Minimum 1 pc(s).

Price informations >



Grinding wheel dresser

Diamond



In stock Immediate delivery Purchase > Minimum 1 pc(s). Price informations >

Options equipment >



Vario conversion with machine base

GU 1 - 1.5 kW

With cyclone suction. Enables the speed of the grinder to be infinitely variable

Article number > Availability > Purchase > In-house production Minimum 1 pc(s). 3491530 - available at short

notice

OPTIMUM[®]

Price informations >



Vario conversion with machine base

GU 3 - 1.5 kW

3491531

Enables the speed of the grinder to be controlled steplessly

Article number > Availability > Purchase >

> In-house production Minimum 1 pc(s). - available at short

notice

OPTIMUM°

Price informations >

Prices on this data sheet are recommended retail prices, subject to change, in €, plus VAT at the statutory rate, plus packaging, shipping, transport, unloading, assembly and, if applicable, instruction costs. Sales prices of the dealers can deviate. No liability is accepted for printing errors, mistakes or incorrect presentation. Technical and optical changes are reserved. Illustration partly with optional accessories.