

Sliding table saw

FKS 315-2000 E

Robust and precise, with swivel saw blade and pre-cutting device



Article number

5900317

Brand

Holzstar

Availability

In stock
Immediate delivery

Catalog directory

Woodworking machinery » Circular saw /
Sliding table saws » Sliding table saws »
FKS




Purchase

Minimum 1 pc(s).


Delivery content

- Sliding tray with boom
- Roll of material on the boom
- Rip fence with round bar guide and fine adjustment
- table extension
- table extension
- flip stop
- edging shoe
- Eccentric
- Scoring unit
- Saw blade guard with suction hose
- Saw blade 315 x 30 x 3 mm 24 teeth
- Scoring saw blade 90 x 20 x 3 mm 12 teeth

Shipping informations

Packaging Metrics		Weights		Delivery		Other	
Length	n/a	Gross	325 kg	Delivery	Carrier	DualUse	
Width	n/a	Net	275 kg	Content	1 pc(s).	SCIP	n/a
Height	n/a					SVHC	No

Root data

Country of origin	EAN	Custom number	Quantity unit
 China	4036351053736	84659120	pc(s).

Description ▼

- Standard with Vorritzeinrichtung
- From -45° to $+45^\circ$ swiveling, extendable telescopic stop with finely adjustable stop flap
- Robust and precise design with sliding carriage
- The gray cast iron work table enables low-vibration work
- Saw blade height adjustment via a handwheel
- Saw blade pivoting from 90 to 45° adjustable via handwheel with scale
- Stable sawing unit guarantees vibration-free and precise work
- Solid boom table with roller and telescopic arm for maximum stability
- Miter fence and hold-down over the entire length of the carriage slidable
- Large aluminum rip fence on round rod guide with fine adjustment
- Strong drive motor for constant cutting speed, even at 100 mm cutting height
- Large dimensioned worktable and standard table extension for cutting widths up to 1220 mm

Media informations ▼






Technical data ▼

Dimensions and weights			
Length (product) approx.	4330 mm	Width/depth (product) approx.	4155 mm
Height (product) approx.	1150 mm	Net weight approx.	275 kg
Extraction port			
Extraction port diameter bottom	100 mm	Saw blade protection extraction port diameter	38 mm
Electrical Data			
Supply voltage	400 V	Mains frequency	50 Hz
Absorbed power drive motor	3.5 kW	Delivery power	3,0 kW
Sliding carriage and table			
Table length	680 mm	Table width	580 mm
Work height	870 mm		
Circular saw unit			
Max. cutting width with rip fence	1220 mm	Trimming length	2000 mm
Saw blade angle	$90 - 45^\circ$	Max. cutting height 90°	100 mm
Max. cutting height 45°	80 mm	(Main) saw blade diameter	315 mm
(Main) saw blade speed	4000 min^{-1}		

Pre-scoring unit

Diameter scoring saw blade	90 mm	Scoring saw blade speed	5800 min ⁻¹
----------------------------	-------	-------------------------	------------------------

Equipment

Table broadening		Table lengthening	
Saw blade cover			


Accessories



Cut-to-size alternating teeth circular saw blade

KSB-WZ 315/28

Highest quality level especially for industrial applications on stationary machines

Article number 

5263128

Availability 

In stock
Immediate delivery

Purchase 

Minimum 1 pc(s).

Price informations 



Edging and production cut circular saw blade

KSB-BF 315/48

Highest quality level especially for industrial applications on stationary machines

Article number 

5263148

Availability 

In stock
Immediate delivery

Purchase 

Minimum 1 pc(s).

Price informations 



Edging and production cut circular saw blade

KSB-BF 315/60

Highest quality level especially for industrial applications on stationary machines

Article number 

5263160

Availability 

In stock
Immediate delivery

Purchase 

Minimum 1 pc(s).

Price informations 



Scoring saw blade

90 x 20 x 3 mm

Article number 

5910090

Availability 

In stock
Immediate delivery

Purchase 

Minimum 1 pc(s).

Price informations 



Prices on this data sheet are recommended retail prices, subject to change, in €, plus VAT at the statutory rate, plus packaging, shipping, transport, unloading, assembly and, if applicable, instruction costs. Sales prices of the dealers can deviate. No liability is accepted for printing errors, mistakes or incorrect presentation. Technical and optical changes are reserved. Illustration partly with optional accessories.