

Portable TIG AC/DC Inverter

EASY-TIG 201 AC/DC PULSE

For workshop and mobile use

Article number V 1074021

Brand ✓ Schweisskraft

Availability v In stock Immediate delivery

Catalog directory → Welding technology » TIG welding machines » TIG inverter EASY-TIG

Purchase V Minimum 1 pc(s).





Delivery content v

- Gas hose 4m incl. Quick connector
- Burner TIG 26 4m
- 3m earth cable 25 mm² with ground terminal

Shipping informations ~

Packaging Metrics		Weights		Delivery		Other	
Length	560 mm	Gross	13.4 kg	Delivery	Carrier	DualUse	×
Width	300 mm	Net	7 kg	Content	1 pc(s).	SCIP	n/a
Height	360 mm					SVHC	No

Root data 🗸

Country of origin	EAN	Custom number	Quantity unit
*) China	4036351250166	85153990	pc(s).

Video 🗸

www.youtube.com/watch?v=-DURwEvMXqM

Description 🗸

- All devices are built in modern inverter technology
- Ideally suited for assembly work (on the ladder, on the scaffolding, ...) and, with protection class IP 21 S, generally also for outdoor work
- Accurate setting of welding parameters via digital display
- Universally applicable for welding of all common electrode types
- Suitable for use on the generator for example in company workshops, schools, metal construction, on construction sites or for farmers
- TIG pulses enable welding with reduced heat input
- HF high-frequency ignition ignites during TIG welding without touching the workpiece
- The quietly running fan dissipates the heat well out of the devices, thus achieving a long duty cycle
- Adjustable welding curve
- Two-year Schweißkraft warranty

Media informations v





Technical data 🗸

i echinical uata 🗸			
Dimensions and weights			
Length (product) approx.	460 mm	Width/depth (product) approx.	150 mm
Height (product) approx.	280 mm	Net weight approx.	9 kg
Setting range			
Setting range TIG DC	10 – 170 A	Electrode adjustment range	10 – 170 A
Duty cycle			
Duty cycle at Imax. 40°C TIG DC	40 %	Duty cycle at max. current 40°C Electrode	30 %
Current at 100% DC 40°C TIG DC	110 A	Current at ED 100% 40°C Electrode	95 A
Electrical Data			
Supply voltage	230±10% V	Mains frequency	50/60 Hz
Power factor	0.6 cos phi	Current consumption TIG AC	34 A
Input current TIG DC	29.1 A	Input current electrode AC	40.2 A
Current consumption electrode DC	42.9 A		
Electrode			
Weldable electrodes	1.6 – 4.0 mm		
Device data			
Pulse rate	0.5 – 200 Hz	Ignition	high frequency
Torch cooling	gas		
Standards and certifications			
Standard	EN 60974-1:2012/EN 60974-10:2014	EMC class	A
Explanation EMC class	This Class A welding equipment is not intended for use in residential areas where power is supplied by a public low-voltage power supply system.		
Power consumption			
Power consumption TIG	4 kVA	Power consumption electrode	5.9 kVA
Electrical connections			
Required generator output	>9.8 kVA	Positive mains voltage tolerance	10 %

Negative mains voltage tolerance	10 %	Open circuit voltage	AC TIG 73.4/DC TIG 69.8/AC MMA 69.3/DC MMA 69.3 V
Connection cable length	2,2 m		

Accessories 🗸

0	Control cable complete with plug Article number 1104011 In stock Immediate delivery	Purchase → Minimum 1 pc(s).	Price informations V
T	TIG welding torch, gas-cooled SR 26 8 mArticle number < 1104008Availability < No stock available 	Purchase 	Price informations ✓ Revoked article
4	TIG welding torch, gas-cooled SR 26 8 m, Up/DownArticle number < 1104018Availability < No stock available Information: Next availability Unknown	Purchase 	Price informations V Revoked article
	Wear parts set VTS SR 17/18/26 Article number V 1100152 Availability V In stock Immediate delivery	Purchase ∨ Minimum 1 pc(s).	Price informations
	Adapter/union nut 1/4" external thread x M12x1 in conical sealing Article number 1104001 Availability In stock Immediate delivery	nternal thread, Purchase ❤ Minimum 1 pc(s).	Price informations

T	TIG welding torch, gas-cooled SR 26 4 mArticle number ▼ 1104004Availability ▼ No stock available Information: Next availability Unknown	Purchase 	Contractions → Revoked article
4	TIG welding torch, gas-cooled SR 26 4 m, Up/DownArticle number <	Purchase ∨ Minimum 1 pc(s).	Conversion Conversio
	Control wire connector 12-pin incl. contact pins Article number Availability 1104012 In stock Immediate delivery	Purchase → Minimum 1 pc(s).	Price informations ↓
est e	Foot remote control with 5 m c cable Article number 1174009 In stock Immediate delivery	Purchase ∨ Minimum 1 pc(s).	Price informations
	Pressure reducerArgon/CO2, largeArticle number 1700050In stockImmediate delivery	Purchase 	Price informations V
8-	Welding cable complete with e SK4 / 25 KS13 EH260Article number < 1250361Availability < In stock Immediate delivery	Purchase ∨ Minimum 1 pc(s).	Price informations V
	Torch connectorSR 26Article number <1174020In stock Immediate delivery	Purchase 	Price informations 🗸

Prices on this data sheet are recommended retail prices, subject to change, in €, plus VAT at the statutory rate, plus packaging, shipping, transport, unloading, assembly and, if applicable, instruction costs. Sales prices of the dealers can deviate. No liability is accepted for printing errors, mistakes or incorrect presentation. Technical and optical changes are reserved. Illustration partly with optional accessories.