DATASHEET

Wide belt sander

BBS 630 C

Compact machine with optimum price-performance ratio

Article number >

5343065

Brand >

Holzkraft

Availability >

No stock available Information: Next availability Unknown

Catalog directory >

Woodworking machinery » Grinding machines for wood » Wide Belt Sanders » Series BBS

Purchase >

Minimum 1 pc(s).

Shipping informations >

Packaging Metrics		Weights		Delivery		Other	
Length	1,200 mm	Gross	582 kg	Delivery	Carrier	DualUse	×
Width	1,020 mm	Net	582 kg	Content	1 pc(s).	SCIP	n/a
Height	1,590 mm					SVHC	No

Root data 🗸

Country of origin	EAN	Custom number	Quantity unit
Czech Republic	4036351038672	84659300	pc(s).

Description ~

- · For processing of small parts, especially solid wood
- Simple and safe operation
- · Combination sanding unit with sanding shoe for fine sanding of solid wood
- Control panel on the front
- Standard with ribbed steel roller Ø 120 mm for calibrating and hard sanding shoe with graphite coating on exchangeable insert
- · Motorized height adjustment of the work table
- Electronically controlled sanding belt oscillation
- · Automatic star / delta starting of the motor
- Digital display of the table position
- · Ammeter for displaying the current consumption of the sanding unit
- Two feed belt speeds
- · Electromagnetic brake





Media informations >





Combination unit for calibrating and sanding

- Ribbed steel roller Ø 120 mm with height fine adjustment
- Hard sanding pad with graphite pad
- Universal version for calibration and sanding of solid wood



Control panel on the front

- Control of the table height
- Digital display of the table position
- Setting the feed speed
- Display of the Current consumption of the sanding unit via ammeter

Technical data >

Dimensions and weights			
Length (product) approx.	1200 mm	Width/depth (product) approx.	1020 mm
Height (product) approx.	1590 mm	Net weight approx.	582 kg
Extraction port			
Extraction performance	2500 m³/h Extraction port diameter		150 mm
Electrical Data			
Feed motor output	0.4/0.6 kW	Drive motor output	5 kW
Supply voltage	400 V	Mains frequency	50 Hz
Height adjustment motor power	0.18 kW		
Pneumatic connection			
Compressed-air consumption	20 l/min	Explanation about compressed-air consumption	without fan
Operating pressure	5.5 bar		
Sanding machine			
Sanding belt length	1600 mm	Sanding belt width	650 mm
Circumferential belt speed(s)	18,5 m/s	Max. sanding width	630 mm
Feed unit			
Feed speed	4.5 / 9 m/min		
Workpiece			
Min. workpiece height	3 mm	Max. workpiece height	160 mm

Accessories v



Wide belt with paper backing 1600x650 K100



5356510

Article number > Availability > Purchase > In stock Minimum 1 PU (5 Immediate delivery pc(s).)

Price informations >



Wide belt with paper backing 1600x650 K120



Article number Availability 5356512

In stock Immediate delivery pc(s).)

Purchase 🗸 Minimum 1 PU (5 Price informations >



Wide belt with paper backing 1600x650 K150



Article number Availability 5356515

Purchase > In stock Minimum 1 PU (5 Immediate delivery pc(s).)

Price informations >



Wide belt with paper backing 1600x650 K180



Article number > Availability > 5356518

Purchase > Minimum 1 PU (5 In stock Immediate delivery pc(s).)

Price informations >



Wide belt with paper backing

In stock

/holzkraft

1600x650 K60

Article number > Availability > 5356506

Purchase > Minimum 1 PU (5 Immediate delivery pc(s).)

Price informations >



Wide belt with paper backing



1600x650 K80

Article number > 5356508

Availability > No stock available Information: Next availability Unknown

Purchase > Minimum 1 PU (5 pc(s).)

Price informations >

Options equipment >



Rubberized roller



Ø 120 mm (45 Sh)

Article number > Availability > 5343070

No stock available Information: Next availability Unknown

Purchase > Minimum 1 pc(s). Price informations >



Rubberized roller



Ø 120 mm (45 Sh)

5343071

Article number > Availability > No stock available Information:

Next availability Unknown

Purchase > Minimum 1 pc(s). Price informations >

Prices on this data sheet are recommended retail prices, subject to change, in €, plus VAT at the statutory rate, plus packaging, shipping, transport, unloading, assembly and, if applicable, instruction costs. Sales prices of the dealers can deviate. No liability is accepted for printing errors, mistakes or incorrect presentation. Technical and optical changes are reserved. Illustration partly with optional accessories.