# DATASHEET

# Edge bander

# minimax me 35 t s



For plastic edges from 0.4 - 3 mm, solid wood edges up to 5 mm and workpieces from 8 - 50 mm

## Article number >

5507235

#### Brand >

Holzkraft

#### Availability >

In stock Immediate delivery

#### Catalog directory >

Woodworking machinery » Edge banding machines » Edge banding machines

#### Purchase >

Minimum 1 pc(s).



### Shipping informations >

Packaging Me	etrics	Weights		Delivery		Other	
Length	3,314 mm	Gross	623 kg	Delivery	Carrier	DualUse	×
Width	1,085 mm	Net	623 kg	Content	1 pc(s).	SCIP	n/a
Height	1,300 mm					SVHC	No

#### Root data 🗸

Country of origin	EAN	Custom number	Quantity unit
Italy	4036351337805	84659900	pc(s).



#### Description >

- Top equipment for high productivity with low space requirements!
- Intuitive operation with the eye-S control and 10" large touch screen: HMI Maestro Active Edge; Graphic display of
  all machining units and their operating status; Graphic simulation of machining operations; Control of all machining
  units; Glue tank temperature regulation; Assistance functions for setting up the machine according to the
  machining program; Fault diagnosis for quick correction of simple errors; Statistics on machining parameters;
  USB connection; Preparation for network connection; Preparation for Industry 4.0 with data transmission protocol
  API REST
- Excellent accessibility to the working units thanks to the large hood, which ensures protection and noise reduction
- Monobloc steel construction ensures high stability and rigidity of the machine
- Automatic aggregate positioning when changing the slab thickness
- Automatic application of strip edges with edge magazine (me 35 t s): The strip edges of solid wood are automatically loaded and synchronized with the board guide
- Panel feed is made by feed chain with rubber glides
- Extendable workpiece support
- · Quality Made in Italy
- Adjustment of the infeed guide using spacer plates

#### Media informations >





#### Operation via eye-S control

- Optimal machine management with Maestro active edge
- Intuitive operation via 10" touchscreen
- Graphic display of all machine functions





#### Anti-adhesive spray unit

• For easy removal of glue residue

#### **Pre-milling unit**

• Two dia cutters





#### Edge preheating device (Fig. shows me 35 t s)

- High-strength bonding thanks to preheating of the workpiece
- me 35 tr s: More efficient preheating of the panel edge with a ceramic infrared lamp

#### Glue station

- The glue is heated quickly and evenly by heating rods located both in the glue pot and in the glue application roller
- Automatic temperature reduction when the machine is idle for a long time
- Glue container Teflon-coated for easy glue change
- Device for recycling unused glue
- Automatic application of the roll edges with trimming knife for edges up to 3mm
- Self-lubrication of the glue pot



# Improved pressing unit for higher quality of the glue line

- Large metal roller, spring-loaded, for good heat dissipation so that the glue sets faster
- Small rubber roller that nestles perfectly around the edging material and presses it over the entire surface



#### Flush radius trimming unit

- With feeler rollers in horizontal and vertical direction for optimal tool positioning
- With combination milling tool Ø55.3mm for flush milling of edges up to 5mm and radius edges up to 2mm
- · Precise adjustment via two digital Show
- With chip extraction



#### Radius scraper


- With numeric position display
- For the perfect finishing of plastic edges
- With device for resetting the unit when not in use



#### Surface scraper

- Absolute cleanliness
- With rotating copying device
- For the perfect finish of the surfaces on the workpiece surface





**Buffing unit** 

Plate transport by feed chain

- Powered by two independent tilting and heightadjustable motors
- For perfect cleaning and polishing of the panel edges

#### Technical data 🗸

Length (product) approx         3314 mm         Width/depth (product) approx         1085 mm           Height (product) approx         1300 mm         Net weight approx         623 kg           Flush radius milling unit           Flush radius milling unit current draw         2 x 0.35 kW         Flush radius milling unit miller appeal         55.3 mm           Flush radius milling unit miller speed         12000 min <sup>-1</sup> Flush radius milling unit extraction appeal a	Dimensions and weights			
Flush radius milling unit Flush radius milling unit current draw 2 x 0.35 kW Flush radius milling unit miller speed 12000 min⁻¹ Flush radius milling unit extraction port diameter HM Flush radius milling unit miller speed 12000 min⁻¹ Flush radius milling unit extraction 2 x 60 mm port diameter  Supply voltage 400 V Mains frequency 50 Hz Gluing unit Glue pot current draw 0.25 kW Glue pot operating temperature 190 °C Glue pot extraction port diameter 60 mm Glue pot filling quantity 0.8 kg Pneumatic connection Operating pressure 6.5 bar Air consumption 470 l/min Feed Feed current draw 0.55 kW Feed speed 7 m/min Edges Edge thickness reel material 0.4 − 3.0 mm Edge thickness strip material 0.5 − 5 mm Pre-milling unit Pre-milling unit extraction port Ø 2 x 80 mm Pre-milling unit current draw 3 kW Pre-milling unit milling speed 7 200 min⁻¹ Pre-milling unit diamond milling Ø 80 mm Pre-milling unit milling height 56 mm Pre-milling unit material removal 0.5 / 1 / 1.5 / 2 mm Scraper blade units	Length (product) approx.	3314 mm	Width/depth (product) approx.	1085 mm
Flush radius milling unit current draw 2 x 0.35 kW flush radius milling unit miller diameter HM  Flush radius milling unit miller speed 12000 min flush radius milling unit extraction port diameter HM  Supply voltage 400 V Mains frequency 50 Hz  Glue pot current draw 0.25 kW Glue pot operating temperature 190 °C Glue pot extraction port diameter 60 mm Glue pot filling quantity 0.8 kg  Pneumatic connection  Operating pressure 6.5 bar Air consumption 470 l/min Feed  Feed current draw 0.55 kW Feed speed 7 m/min Edges  Edge thickness reel material 0.4 − 3.0 mm Edge thickness strip material 0.5 − 5 mm  Pre-milling unit extraction port Ø 2 x 80 mm Pre-milling unit current draw 3 kW Pre-milling unit milling speed 7200 min Pre-milling unit diamond milling Ø 80 mm Pre-milling unit milling height 56 mm Pre-milling unit material removal 0.5 / 1 / 1.5 / 2 mm  Scraper blade units  Fadius scraper 2 mm	Height (product) approx.	1300 mm	Net weight approx.	623 kg
Flush radius milling unit miller speed 12000 min Flush radius milling unit extraction port diameter  Glue pot current draw 0.25 kW Glue pot operating temperature 190 °C Glue pot extraction port diameter 60 mm Glue pot filling quantity 0.8 kg Pneumatic connection  Operating pressure 6.5 bar Air consumption 470 l/min Feed  Feed current draw 0.55 kW Feed speed 7 m/min Edges  Edge thickness reel material 0.4 – 3.0 mm Edge thickness strip material 0.5 – 5 mm Pre-milling unit extraction port Ø 2 x 80 mm Pre-milling unit current draw 3 kW Pre-milling speed 7200 min Pre-milling unit milling speed 7200 min Pre-milling unit milling height 56 mm Pre-milling unit material removal 0.5 / 1 / 1.5 / 2 mm Scraper blade units  Radius scraper 2 mm Flue with saints and sure is a flue with the straction port with the straction in t	Flush radius milling unit			
Electrical Data   Supply voltage 400 V Mains frequency 50 Hz   Gluing unit   Glue pot current draw 0.25 kW Glue pot operating temperature 190 °C   Glue pot extraction port diameter 60 mm Glue pot filling quantity 0.8 kg   Pneumatic connection   Operating pressure 6.5 bar Air consumption 470 l/min   Feed   Feed current draw 0.55 kW Feed speed 7 m/min   Edges   Edge thickness reel material 0.4 – 3.0 mm Edge thickness strip material 0.5 – 5 mm   Pre-milling unit   Pre-milling unit extraction port ∅ 2 x 80 mm Pre-milling unit current draw 3 kW   Pre-milling unit milling speed 7200 min⁻¹ Pre-milling unit diamond milling Ø 80 mm   Pre-milling unit milling height 56 mm Pre-milling unit material removal 0.5/1/1.5/2 mm   Scraper blade units   Radius scraper 2 mm Elementary milling speed 0.5/1/1.5/2 mm	Flush radius milling unit current draw	2 x 0.35 kW		55.3 mm
Supply voltage400 VMains frequency50 HzGluing unitGlue pot current draw0.25 kWGlue pot operating temperature190 °CGlue pot extraction port diameter60 mmGlue pot filling quantity0.8 kgPneumatic connectionOperating pressure6.5 barAir consumption470 l/minFeedFeed current draw0.55 kWFeed speed7 m/minEdgesEdge thickness reel material0.4 – 3.0 mmEdge thickness strip material0.5 – 5 mmPre-milling unitPre-milling unit extraction port Ø2 x 80 mmPre-milling unit current draw3 kWPre-milling unit milling speed7200 min or 1Pre-milling unit diamond milling Ø80 mmPre-milling unit milling height56 mmPre-milling unit material removal0.5 / 1 / 1.5 / 2 mmScraper blade unitsRadius scraper2 mm	Flush radius milling unit miller speed	12000 min <sup>-1</sup>		2 x 60 mm
Glue pot current draw 0.25 kW Glue pot operating temperature 190 °C Glue pot extraction port diameter 60 mm Glue pot filling quantity 0.8 kg  Preumatic connection  Operating pressure 6.5 bar Air consumption 470 l/min  Feed  Feed current draw 0.55 kW Feed speed 7 m/min  Edges  Edge thickness reel material 0.4 – 3.0 mm Edge thickness strip material 0.5 – 5 mm  Pre-milling unit  Pre-milling unit extraction port Ø 2 x 80 mm Pre-milling unit current draw 3 kW  Pre-milling unit milling speed 7200 min Pre-milling unit diamond milling Ø 80 mm  Pre-milling unit milling height 56 mm Pre-milling unit material removal 0.5 / 1 / 1.5 / 2 mm  Scraper blade units  Radius scraper 2 mm	Electrical Data			
Glue pot current draw 0.25 kW Glue pot operating temperature 190 °C Glue pot extraction port diameter 60 mm Glue pot filling quantity 0.8 kg  Pneumatic connection  Operating pressure 6.5 bar Air consumption 470 l/min  Feed  Feed current draw 0.55 kW Feed speed 7 m/min  Edges  Edge thickness reel material 0.4 – 3.0 mm Edge thickness strip material 0.5 – 5 mm  Pre-milling unit  Pre-milling unit extraction port Ø 2 x 80 mm Pre-milling unit current draw 3 kW  Pre-milling unit milling speed 7200 min <sup>-1</sup> Pre-milling unit diamond milling Ø 80 mm  Pre-milling unit milling height 56 mm Pre-milling unit material removal 0.5 / 1 / 1.5 / 2 mm  Scraper blade units  Radius scraper 2 mm	Supply voltage	400 V	Mains frequency	50 Hz
Glue pot extraction port diameter 60 mm Glue pot filling quantity 0.8 kg  Pneumatic connection  Operating pressure 6.5 bar Air consumption 470 l/min  Feed  Feed current draw 0.55 kW Feed speed 7 m/min  Edges  Edge thickness reel material 0.4 – 3.0 mm Edge thickness strip material 0.5 – 5 mm  Pre-milling unit  Pre-milling unit extraction port Ø 2 x 80 mm Pre-milling unit current draw 3 kW  Pre-milling unit milling speed 7200 min Pre-milling unit diamond milling Ø 80 mm  Pre-milling unit milling height 56 mm Pre-milling unit material removal 0.5 / 1 / 1.5 / 2 mm  Scraper blade units  Radius scraper 2 mm	Gluing unit			
Pneumatic connection         Operating pressure       6.5 bar       Air consumption       470 l/min         Feed         Feed current draw       0.55 kW       Feed speed       7 m/min         Edges         Edge thickness reel material       0.4 – 3.0 mm       Edge thickness strip material       0.5 – 5 mm         Pre-milling unit         Pre-milling unit extraction port Ø       2 x 80 mm       Pre-milling unit current draw       3 kW         Pre-milling unit milling speed       7200 min <sup>-1</sup> Pre-milling unit diamond milling Ø       80 mm         Pre-milling unit milling height       56 mm       Pre-milling unit material removal       0.5/1/1.5/2 mm         Scraper blade units         Radius scraper       2 mm	Glue pot current draw	0.25 kW	Glue pot operating temperature	190 °C
Operating pressure       6.5 bar       Air consumption       470 l/min         Feed         Feed current draw       0.55 kW       Feed speed       7 m/min         Edges         Edge thickness reel material       0.4 − 3.0 mm       Edge thickness strip material       0.5 − 5 mm         Pre-milling unit         Pre-milling unit extraction port Ø       2 x 80 mm       Pre-milling unit current draw       3 kW         Pre-milling unit milling speed       7200 min⁻¹¹       Pre-milling unit diamond milling Ø       80 mm         Pre-milling unit milling height       56 mm       Pre-milling unit material removal       0.5 / 1 / 1.5 / 2 mm         Scraper blade units         Radius scraper       2 mm	Glue pot extraction port diameter	60 mm	Glue pot filling quantity	0.8 kg
Feed current draw 0.55 kW Feed speed 7 m/min  Edges  Edge thickness reel material 0.4 – 3.0 mm Edge thickness strip material 0.5 – 5 mm  Pre-milling unit  Pre-milling unit extraction port Ø 2 x 80 mm Pre-milling unit current draw 3 kW  Pre-milling unit milling speed 7200 min Pre-milling unit diamond milling Ø 80 mm  Pre-milling unit milling height 56 mm Pre-milling unit material removal 0.5 / 1 / 1.5 / 2 mm  Scraper blade units  Radius scraper 2 mm	Pneumatic connection			
Feed current draw 0.55 kW Feed speed 7 m/min Edges  Edge thickness reel material 0.4 − 3.0 mm Edge thickness strip material 0.5 − 5 mm Pre-milling unit  Pre-milling unit extraction port Ø 2 x 80 mm Pre-milling unit current draw 3 kW Pre-milling unit milling speed 7200 min Pre-milling unit diamond milling Ø 80 mm Pre-milling unit milling height 56 mm Pre-milling unit material removal 0.5 / 1 / 1.5 / 2 mm Scraper blade units  Radius scraper 2 mm	Operating pressure	6.5 bar	Air consumption	470 l/min
Edge thickness reel material 0.4 – 3.0 mm Edge thickness strip material 0.5 – 5 mm  Pre-milling unit  Pre-milling unit extraction port Ø 2 x 80 mm Pre-milling unit current draw 3 kW  Pre-milling unit milling speed 7200 min Pre-milling unit diamond milling Ø 80 mm  Pre-milling unit milling height 56 mm Pre-milling unit material removal 0.5 / 1 / 1.5 / 2 mm  Scraper blade units  Radius scraper 2 mm	Feed			
Edge thickness reel material 0.4 – 3.0 mm Edge thickness strip material 0.5 – 5 mm  Pre-milling unit  Pre-milling unit extraction port Ø 2 x 80 mm Pre-milling unit current draw 3 kW  Pre-milling unit milling speed 7200 min <sup>-1</sup> Pre-milling unit diamond milling Ø 80 mm  Pre-milling unit milling height 56 mm Pre-milling unit material removal 0.5 / 1 / 1.5 / 2 mm  Scraper blade units  Radius scraper 2 mm	Feed current draw	0.55 kW	Feed speed	7 m/min
Pre-milling unit extraction port Ø 2 x 80 mm Pre-milling unit current draw 3 kW Pre-milling unit milling speed 7200 min <sup>-1</sup> Pre-milling unit diamond milling Ø 80 mm Pre-milling unit milling height 56 mm Pre-milling unit material removal 0.5 / 1 / 1.5 / 2 mm  Scraper blade units Radius scraper 2 mm	Edges			
Pre-milling unit extraction port Ø 2 x 80 mm Pre-milling unit current draw 3 kW  Pre-milling unit milling speed 7200 min <sup>-1</sup> Pre-milling unit diamond milling Ø 80 mm  Pre-milling unit milling height 56 mm Pre-milling unit material removal 0.5 / 1 / 1.5 / 2 mm  Scraper blade units  Radius scraper 2 mm	Edge thickness reel material	0.4 – 3.0 mm	Edge thickness strip material	0.5 – 5 mm
Pre-milling unit milling speed 7200 min <sup>-1</sup> Pre-milling unit diamond milling Ø 80 mm  Pre-milling unit milling height 56 mm Pre-milling unit material removal 0.5 / 1 / 1.5 / 2 mm  Scraper blade units  Radius scraper 2 mm	Pre-milling unit			
Pre-milling unit milling height 56 mm Pre-milling unit material removal 0.5 / 1 / 1.5 / 2 mm  Scraper blade units  Radius scraper 2 mm	Pre-milling unit extraction port Ø	2 x 80 mm	Pre-milling unit current draw	3 kW
Scraper blade units Radius scraper 2 mm	Pre-milling unit milling speed	7200 min <sup>-1</sup>	Pre-milling unit diamond milling Ø	80 mm
Radius scraper 2 mm	Pre-milling unit milling height	56 mm	Pre-milling unit material removal	0.5 / 1 / 1.5 / 2 mm
	Scraper blade units			
Buffing unit	Radius scraper	2 mm		
	Buffing unit			

Buffing unit current draw	2 x 0.14 kW	Buffing unit speed	2800 min <sup></sup> 1
Workpiece			
Workpiece thickness	8 – 50 mm	Minimum length of workpiece	120 mm
Min. work piece width	110 mm		

#### Equipment >

Roller edge rotary platen 730		Edge magazine
Anti-adhesive spraying unit	✓	Pre-milling unit with two dia cutters
Edge preheating device	With heating plate	Glue container quick-change   kit  ✓
Bonding unit	•	Combination unit flush trimming / round corners
Flush radius milling unit	✓	Radius scraper unit With numerical position display
Area scraper unit	With rotating copying device	Buffing unit

#### Accessories v



#### **Melt adhesive**

5 kg

Article number ✓ 5517023

Availability 
In stock
Immediate delivery

Purchase ✓ Minimum 1 pc(s).

Purchase >

Minimum 1 pc(s).

Holzkarbeitungsmaschinen

Price informations >



#### Melt adhesive

25 kg

Article number ➤ Availability ➤ 5517024 No stock availa

No stock available Information:
Next availability
Unknown

Zholzkraft'

Price informations **∨** 



## Diamond tools for jointing cutter

Article number **→** 5514565

Availability 
No stock available Information:
Next availability

Unknown

Purchase ✓
Minimum 1 pc(s).

Aholzkiaft Holzbearbeitungsmaschinen

Price informations >



## **Tool Kit**

Radius 1 mm

Article number ➤ 5514564

Availability 
No stock available Information:
Next availability
Unknown

Purchase ✓ Minimum 1 pc(s).

Price informations >

**Z**holzkraft



## **Tool Kit** Radius 1.5 mm



**Z**holzkraft

Article number > Availability > 5514563

No stock available Information: Next availability Unknown

Purchase > Minimum 1 pc(s). Price informations >



**Tool Kit** Radius 3 mm

Article number > 5514562

Availability > No stock available Information: Next availability Unknown

Purchase > Minimum 1 pc(s). Price informations >



Glue container interchangeable for EVA-glue

Article number > Availability > 5514576

No stock available Information: Next availability Unknown

Purchase > Minimum 1 pc(s). Price informations >

**/**holzkraft

**Z**holzkraft



Glue container

interchangeable for polyurethane glue with rapid drainage

Article number > 5514585

Availability > No stock available Information: Next availability Unknown

Purchase > Minimum 1 pc(s). Price informations >



Connection set for extraction unit

For minimax me 35 und me 40

5146070

Article number **→** Availability **→** No stock available Information: Next availability Expected on calendar week 48/2023

Purchase > Minimum 1 pc(s).

Price informations >

**Zholzkraft** 

Options equipment >



# Option grooving unit

Groove width 4 mm



Availability > No stock available Information: Next availability Unknown



Minimum 1 pc(s).



**/holzkraft** 

**Pholzkraft** 



#### Glue container

Polyurethane glue with rapid drainage

Article number > Availability > 5514586 No stock available

Information: Next availability Unknown

Purchase > Minimum 1 pc(s). Price informations >



## **Ceramic lamp** With infrared rays

Article number > 5514587

Availability > No stock available Information: Next availability Unknown

Purchase >

Minimum 1 pc(s).



Price informations >




## **Nesting sensing roller**

Flush milling unit

Article number > Availability > 5514588

In stock Immediate delivery Purchase > Minimum 1 pc(s). **Z**holzkraft





## **Nesting sensing roller**

Scraper unit

Article number > 5514589

Availability > In stock Immediate delivery Purchase > Minimum 1 pc(s).

Price informations >

**Z**holzkraft



#### Interior lighting of the machine

Article number > 5514590

Availability > No stock available Information: Next availability Unknown

Purchase > Minimum 1 pc(s).

**Zholzkiaft** Price informations >





## Barcode reader Wireless



Article number ➤ Availability ➤ 5519004 In stock

Availability 
In stock
Immediate delivery

Purchase ➤ Minimum 1 pc(s).

Price informations >

Prices on this data sheet are recommended retail prices, subject to change, in €, plus VAT at the statutory rate, plus packaging, shipping, transport, unloading, assembly and, if applicable, instruction costs. Sales prices of the dealers can deviate. No liability is accepted for printing errors, mistakes or incorrect presentation. Technical and optical changes are reserved. Illustration partly with optional accessories.