

Short log splitter HSE 8-550 (230V)



Wood splitter HSE 8-550 - Short wood splitter for demanding users

Article number ▼

5981008

Brand ▼

Holzkraft

Availability ▼

In stock
Immediate delivery

Catalog directory ▼

Woodworking machinery » Firewood technology » Wood splitter » Wood splitter with electric drive

Purchase ▼


Minimum 1 pc(s).



Shipping informations ▼

Packaging Metrics		Weights		Delivery		Other	
Length	560 mm	Gross	117 kg	Delivery	Carrier	DualUse	✘
Width	400 mm	Net	109.9 kg	Content	1 pc(s).	SCIP	n/a
Height	1,150 mm					SVHC	No

Root data ▼

Country of origin	EAN	Custom number	Quantity unit
 China	4036351267942	84659600	pc(s).

Description ▼

- Available with 230 V or 400 V drive
- Two-hand safety switch
- Robust and solid construction
- Shock and scratch resistant thanks to high quality powder coating
- Convenient transport with a hand drawbar due to the standard chassis with hard rubber wheels and an additional support wheel
- Fast, tool-free gap height adjustment
- 400 V phase-reversing model

Media informations ▼



Technical data ▼

Dimensions and weights			
Length (product) approx.	845 mm	Width/depth (product) approx.	935 mm
Height (product) approx.	1500 mm	Net weight approx.	110 kg
Drive			
Drive motor input	3 kW		
Electrical Data			
Supply voltage	230 V	Mains frequency	50 Hz
Device data			
Max. splitting force	8 t	Max. splitting stroke	485 mm
Max. splitting length	550 mm	Max. split material diameter	300 mm
Advance stroke(s)	3.1 cm/s	Return stroke	17.1 cm/s
Noise emission			
Sound pressure level	≤ 89.7 dB(A)		
Hydraulic system			
Oil tank capacity	4 l		

Prices on this data sheet are recommended retail prices, subject to change, in €, plus VAT at the statutory rate, plus packaging, shipping, transport, unloading, assembly and, if applicable, instruction costs. Sales prices of the dealers can deviate. No liability is accepted for printing errors, mistakes or incorrect presentation. Technical and optical changes are reserved. Illustration partly with optional accessories.