

Electronic battery charger/maintainer

EBC 70 E

for batteries with a charging voltage of 6 or 12 volts



Article number ▼

6851000

Brand ▼

Unicraft

Availability ▼

In stock

Immediate delivery

Catalog directory ▼

Workshop and lifting technology » Battery charging and starting devices » Battery charge / receive device

Purchase ▼

Minimum 1 pc(s).




Delivery content ▼

- Charging cable 0.4 m with quick connector and fully insulated terminals
- Cable 0.4 m with quick connector and ring eyelet terminals

Shipping informations ▼

Packaging Metrics		Weights		Delivery		Other	
Length	147 mm	Gross	0.65 kg	Delivery	Delivery service	DualUse	✘
Width	67 mm	Net	0.5 kg	Content	1 pc(s).	SCIP	n/a
Height	245 mm					SVHC	No

Root data ▼


Country of origin	EAN	Custom number	Quantity unit
 China	4036351320999	85044095	pc(s).

Description ▼

- Battery-saving charging through charging phases automatically matched to the battery condition
- Charging and conservation take place according to special characteristic curves matched to the battery type
- Optimal charging of the battery even at temperatures below 0 °C with special winter mode, device charges with higher charging current and increased charging voltage
- Memory Saver function: In back-up charge mode, use as a power supply unit to retain the settings of the vehicle electronics when the battery is removed
- IP65: device is dustproof and has protection against water jets from any angle

- Different battery types can be selected via the MODE function

Media informations ▼



Technical data ▼

General features			
Performance	70 W	Charging voltage	6 / 12 V
Charging current	2 / 4 A	Charging capacity	4 – 120 Ah
Maintenance capacity	4 – 120 Ah	Charge cycles	10
Start voltage	3 V	Number of operating modes	1
Degree of protection	IP 65		
Dimensions and weights			
Charging cable length	1.1 + 0.4 m	Length (product) approx.	193 mm
Width/depth (product) approx.	85.4 mm	Connecting cable length	1,5 m
Height (product) approx.	52 mm	Net weight approx.	0.5 kg

Electrical Data			
Fuse protection	3.15 A	Supply voltage	230 V
Mains frequency	50 Hz		
Application scope			
Suitable for battery types	Wet, Gel, AGM, Lithium (LiFePO4)	Charging applications	Krad, cars, minibus, vans, trucks<7,5t, boats
Charging	electronic	Receiving	<input type="checkbox"/>
Backup charging operation (memory saver)	<input type="checkbox"/>		

Equipment

Winter mode	<input checked="" type="checkbox"/>	Digital display	Battery voltage, battery status, reverse polarity/short circuit, back-up charge mode on/off, battery type selection.
Reverse polarity short circuit protection	<input checked="" type="checkbox"/>	Thermal protection switch with auto-reset	<input checked="" type="checkbox"/>
Overload protection	<input checked="" type="checkbox"/>	Voltage peak protection	<input checked="" type="checkbox"/>
Charging cable +/- with standard crocodile clips	0.4	Charging cable +/- with M6 eye clamps	0.4
Connecting cable	230 Volt with Schuko plug		

Prices on this data sheet are recommended retail prices, subject to change, in €, plus VAT at the statutory rate, plus packaging, shipping, transport, unloading, assembly and, if applicable, instruction costs. Sales prices of the dealers can deviate. No liability is accepted for printing errors, mistakes or incorrect presentation. Technical and optical changes are reserved. Illustration partly with optional accessories.