

Piston compressor MOBILBOY SILENCE 241/24 OF E



Oil-free, very quiet compressor for mobile use

Article number v 2002245

Brand V Aircraft

Availability 🗸

No stock available Information: Next availability Expected on calendar week 30/2024

Catalog directory v

Compressed air technology » Piston compressors » Mobile piston compressors » MOBILBOY SILENCE

Purchase 🗸

Minimum 1 pc(s).

Shipping informations ~

Packaging Metrics		Weights		Delivery		Other	
Length	585 mm	Gross	25 kg	Delivery	Carrier	DualUse	×
Width	255 mm	Net	23 kg	Content	1 pc(s).	SCIP	n/a
Height	580 mm					SVHC	No

Root data 🗸

Country of origin	EAN	Custom number	Quantity unit
* China	4036351340027	84148022	pc(s).

Description 🗸

- Very smooth operation and therefore very quiet
- · Oil-free piston compressor: no oil change necessary and no oil in the condensate for best working quality
- · Compressed air reducer for stepless adjustment of the desired working pressure
- High-quality pressure switch
- Electric motor equipped with motor protection switch
- Fully automatic on/off operation
- One pressure gauge each for displaying the tank and working pressure
- Powder-coated compressed air tank



Significant Features V



Oil-free

- No oil change necessary
- No oil in condensate



Very quiet Suitable for installation in any working environment

Media informations ~



- Compressed air reducer for stepless adjustment of the desired working pressure
- High-quality pressure switch
- One-hand quick coupling
- One pressure gauge each for displaying the tank and working pressure

Technical data 🗸

General features			
Air outlet	1/4 "		
Dimensions and weights			
Length (product) approx.	600 mm	Width/depth (product) approx.	280 mm
Height (product) approx.	600 mm	Net weight approx.	24 kg
Electrical Data			
Supply voltage	230 V	Mains frequency	50 Hz
Delivery power	1.3 kW	Absorbed power	1.4 kW
Duty cylce drive motor	70 %	 	

Noise emission			
Sound pressure level Lp	62 dB(A)	Explanation sound pressure level Lp	Sound pressure level at 1 m distance according to DIN 45635 T 13
Compressor			
Compressor system	WDS	Oil-free / oil-lubricated	Oil free
Suction capacity approx.	240 l/min	Filling capacity approx.	140 l/min
Explanation filling capacity	at 6 bar working pressure	Number of cylinders	2
Number of compressor stages	1	Compressor speed	1400 min 1
Piston stroke	22 mm	Diameter of piston	69.7 mm
Compressed air tank			
Maximum pressure	10 bar	Pressure vessel capacity	24 I
Tank surface	Powder coated		

Equipment 🗸

Pressure regulation	Pressure regulator	Automatic pressure switch	✓
Drive transmission	Direct-coupled	Material compressed air line	Flexible armored conduit with heat protection
Compressed air outlet	A one-hand quick coupling	Pressure vessel	Powder coated
Compressor base	Two wheels with solid rubber tyres, two rubber buffers	Connection cable	1.5
Connector	CEE 7/4		

Accessories \checkmark



Prices on this data sheet are recommended retail prices, subject to change, in €, plus VAT at the statutory rate, plus packaging, shipping, transport, unloading, assembly and, if applicable, instruction costs. Sales prices of the dealers can deviate. No liability is accepted for printing errors, mistakes or incorrect presentation. Technical and optical changes are reserved. Illustration partly with optional accessories.